ECOseals b.v.

PO Box190
5400 AD UDEN NL

Chamber of Commerce: 58532811
VAT: NL853079079B01

mob: +31 6 43210 349

info@ecoseals.eu
www.ecoseals.eu

The lquid-tight washing area.

Liquid tight provision of strong composite, modular, movable, chemical resistant en durable.

ECO SEALS®

Liquid tight provision of strong **composite, modular, movable, chemical resistant** and **durable**.

Technical specifications:

- Above ground setup and therefore mobile
- Life expectancy> 25 years
- Modular construction of floor plates, up to desired surface
- Easy transport, container size, 10 x lighter than concrete
- Traffic class 600 (for 60 tonnes of traffic, with an axle load of up to 20 tonnes)
- Durable resistant to static and dynamic mechanical loads
- Durable resistant to thermal, physical and chemical influences
- Possibly with screen walls, (washing) installation, HD cleaner etcetera
- Including above-ground sludge trap / separator and waste water pump
- Integrated drainage system with trouble-free sludge handling
- Including in NL an independent inspection and VVV certificate
- No weathering, cracks, deformation or crumbling
- No attack by moisture, mold, rot, temperature or UV
- Use of an existing paving as a foundation basis
- No digging, cunet or piling or heavy foundation required
- CO2 footprint is neutral compared to a concrete floor
- Design according to "cradle to cradle" principle
- ECOseals floor meets the circularity requirements of the current environmental policy

INSPECTION RvA I 129

The mobile liquid-tight composite floor has special qualities for industrial cleaning. The high chemical resistance speaks for itself and is above all very robust. An extremely professional facility with large capacity, suitable for almost every situation. This mobile concept is based on our sustainable, liquid-tight composite floor with many additional features.

ECO SEALS®